

A4 STOCK SPECIALITY SPEC SHEET

MULTIPURPOSE (LASER/COPIER PRODUCTS)



Matt white polyester with a permanent adhesive – BS5609 part 2 approved (MWP)

A matt white polyester (PET) specifically designed for use on 'hot fuse' printer systems. Some slight curl may occur on exiting the printer but this will flatten quickly. This material is primarily used in the area of 'long life' durable, tracking labels. This material also confirms to BS5609 part 2 for marine immersion. (To fully meet the BS5609 standard, independent testing of the label with overprinting included should be conducted).

Face material properties

Grammage	76 gsm
Caliper (thickness)	55 microns

Adhesive

A clear permanent, acrylic based adhesive with good tack & adhesion on a wide range of surfaces. When applied correctly to an appropriate good clean surface this adhesive will allow the label to withstand the rigours of BS5609 Marine Immersion testing.

Minimum application temp.	+0°C
Storage range once applied	-20°C to +80°C

Backing

A one side clay coated, bleached kraft paper with good lay-flatness & stability

Thickness	110 microns
Grammage	98 gsm

Environmental

Paper components are either ECF or TCF grade manufactured using pulp from sustainable, managed resources. All dimensions are nominal target specifications, but may vary. All products within our range are manufactured under ISO9001:2008

Issue: 160210