

## A4 STOCK SPECIALITY SPEC SHEET

### MULTIPURPOSE (LASER/COPIER/INKJET PRODUCTS)



### White Paper with high tack adhesive (HT)

#### Face material properties.

A bright white, surface –sized wood free paper with good opacity  
Suitable for Most print methods. Including, Litho, All forms of dry toner, Ink-Jet Mono and various other digitally based over print systems. It will carry full colour print but is not suited to detailed work and should be assessed in detail before being used in such applications.

Grammage	71gsm
Caliper (thickness)	85 microns

#### Adhesive

A good permanent, high tack acrylic based adhesive with very good initial tack and excellent long term adhesion, over a wide range of surfaces. This adhesive also complies with the German BgVV for indirect food contact & short term contact with dry & moist food. Recommended to be used in conjunction with our Window trim feature.

Minimum application temp.	0°C
Storage range once applied	-20°C to +80°C (up to 120°C for five minutes)

#### Backing

White siliconised Paper. Chosen to aid flatness and feeding characteristics.

Grammage	76gsm
Thickness	71 microns

#### Environmental

Paper components are either ECF or TCF grade manufactured using pulp from sustainable, managed resources. All dimensions are nominal target specifications, but may vary. All products within our range are manufactured under ISO9001:2008

Issue: 160210