


## T10C/ T20C/ T30C Label Rewinder Family

### The Rewinder Everyone Can Use


The T10C/ T20C/ T30C rewriter has an idler arm that can be positioned to rewind labels from either side of the printer. Depending on the user's requirements, the rewriter can rewind "inside or outside" label rolls.



Modular core adaptor fits 1", 1.5" & 3" core sizes



Colored LED indicator provides rewriter operation status



Rewinding direction switch to rewind "inside or outside" label rolls



Easy assembly lock module for quickly and firmly label roll holding

Model	T10C	T20C	T30C
Paper width	4.72" (Max.)	7" (Max.)	8.46"
Rewind Speed	Up to 14 IPS	Up to 14 IPS	6 IPS
Label Roll	8" (Max.)	6" (Max.)	6.3" (Max.)
Core Roll	Coreless, 1" (25.2~25.6mm), 1.5"x2 (37.4~38.0mm & 40~40.6mm), 3" (76~76.6mm)		
Label Roll Weight	5 Kg		5.5Kg (12 lb)
Rewinding	Label Inside / Outside		
Switches	Rewind		
Motor	Hybrid Motor		
Power	100~240VAC 24W, 24V Adapter		
Environment	Operating Temp.: 41°F to 104°F(5°C to 40°C) Storage Temp.: -4°F to 122°F(-20°C to 60°C)		
Humidity	10-85% (non-condensing RH)		
Size (H*W*D)	303mm*180mm*349mm	303mm*180mm*394mm	303 mm*230 mm*349 mm
Agency Approvals	CE, FCC Class A		
Weight	5 Kg (11 lb)		5.5Kg (12 lb)

\* Specifications are subject to change without notice. All company and/or product names are trademarks and/or registered trademarks of their respective owners.