### PRODUCT SPEC SHEET

### Zebra LS1203



# Zebra LS1203

### Excellent value for everyday use

The Zebra LS1203 handheld scanner delivers high quality laser scanning, user-friendly ergonomics and durability at an affordable price. Designed to meet the needs of small businesses, the LS1203 provides the performance and features needed to significantly reduce data entry errors and boost productivity day in and day out in gift shops, boutiques, sporting goods, jewelers, video stores, florists and other small local retailers. Easy and comfortable to use, this high-value cost-effective scanner offers the reliability and investment protection that have made Zebra the global leader in handheld bar code scanning.

### Increased productivity from the start

For point of sale check-out applications, the LS1203 provides the power to improve operational efficiencies right out of the box. The plug-and-play design virtually eliminates installation hassles. The intuitive ergonomic design eliminates training requirements — employees are up and running in minutes. Manual keying is eliminated, reducing cashier errors and ensuring that your customers are charged the correct amount. The result is faster checkout, increased customer satisfaction and a quick return on investment. In the back room, the LS1203 automates paper-based processes, such as inventory management, translating into more accurate information and less time spent on day-to-day administrative tasks — and more time spent serving customers.

### **Durable construction combined with future-proofing**

With a single board construction and durable scan element, the LS1203 can easily stand up to daily use and those inevitable drops. With everyday operation you can count on, the LS1203 ensures minimal maintenance costs and maximum uptime. And integrated multiple interfaces provide the investment protection you need to ensure that the scanner you buy today will work with tomorrow's POS system.

### Proven quality you can trust

When you choose the LS1203, you receive the added assurance of purchasing a product from Zebra — the global leader in handheld bar code scanning with millions of scanners in use every day by the world's largest retailers worldwide. And since even the most durable products require a maintenance plan and support strategy, Zebra has designed a full complement of service offerings to help you protect your investment and maintain peak performance. To learn more about how the LS1203 can help your small business, visit www.zebra.com/ls1203 or access our global contact directory at www.zebra.com/contact

## **Zebra LS1203 Specifications**

PHYSICAL CHARACTERISTICS		PERFORMANCE CHARACTERISTICS	
Dimensions:	2.4 in. H x 7.1 in. L x 2.4 in. W 6.2 cm H x 18 cm L x 6 cm W	Scanner Type:	Bi-directional
		Light Source (Laser)	650nm laser diode
Weight (w/o cable):	Approximately 4.3 oz. (122 g)	:	
Voltage & Current:	5 +/-10%VDC @ 100 mA (Stand	Scan Rate:	100 scans per second



### **FEATURES**

Durable construction: single board construction; meets Zebra's stringent 5 ft. drop tests

Designed for continuous usage all day, every day; significantly reduces downtime and repair costs

### Multiple interfaces: RS232, USB, KBW ( keyboard wedge) in one scanner

Simplifies installation and integration; futureproof solution ensures compatibility with your host/ POS today and tomorrow

### Ergonomic hybrid design featuring sleek , lightweight, balanced form factor

Maximum comfort for all day use; reduces user fatigue

# Intuitive scanning; plug and play design

Practically eliminates setup and training time for faster return on investment

### High quality 1D laser scanner — choice of triggered or Auto-Scan™ ( continuous mode) scanning

Accurate first time scanning; always ready for the next scan

by: <35 mA)	Typical Working	See chart below.
Host power or external power supply	Print Contrast Min.:	30% minimum reflectance
Cash Register White or Twilight Black	Roll (Tilt): <sup>1</sup>	± 30° from normal
	Pitch: <sup>2</sup>	± 65°
USER ENVIRONMENT		± 60°
32° to 122° F/0° to 50° C	Decode Capability:	UPC/EAN, UPC/EAN with Supplementals, UPC/EAN 128, Code 39, Code 39 Full ASCII, Code 39 TriOptic, Code 128, Code 128 Full ASCII, Codabar, Interleaved 2 of 5, Discrete 2 of 5, Code 93, MSI, Code 11, IATA, GS1 DataBar (formerly RSS) variants, Chinese 2 of 5
-40° to 158° F/-40° to 70° C		
5% to 95% relative humidity, non-condensing		
Withstands multiple 5 ft./1.524m drops to concrete		
Tolerant to typical artificial indoor and natural outdoor (direct sunlight ) lighting conditions. Fluorescent, Incandescent, Mercury Vapor, Sodium Vapor, LED4: 450 Ft Candles (4,844 Lux) Sunlight: 8000 Ft Candles (86,111 Lux)	Interfaces Supported:	USB, RS-232; Keyboard Wedge
	REGULATORY	
	Electrical Safety:	UL1950, CSA C22.2 No. 950,
User-selectable: three levels	· 	EN60950/IEC950
User-selectable: three tones	Laser Safety:	IEC Class 1
Conforms to 15 kV air discharge and 8 kV of contact discharge	EMI/RFI:	FCC Part 15 Class B, ICES-003 Class B, European Union EMC Directive, Australian SMA, Taiwan EMC, Japan VCCI/MITI/Dentori
	Host power or external power supply  Cash Register White or Twilight Black  NMENT  32° to 122° F/0° to 50° C  -40° to 158° F/-40° to 70° C  5% to 95% relative humidity, non-condensing  Withstands multiple 5 ft./1.524m drops to concrete  Tolerant to typical artificial indoor and natural outdoor (direct sunlight) lighting conditions. Fluorescent, Incandescent, Mercury Vapor, Sodium Vapor, LED4: 450 Ft Candles (4,844 Lux) Sunlight: 8000 Ft Candles (86,111 Lux)  User-selectable: three levels  User-selectable: three tones  Conforms to 15 kV air discharge	Host power or external power supply  Cash Register White or Twilight Black  Pitch:  Skew (Yaw):  Skew (Yaw):  Tolerant to typical artificial indoor and natural outdoor (direct sunlight) lighting conditions. Fluorescent, Incandescent, Mercury Vapor, Sodium Vapor, LED4: 450 Ft Candles (4,844 Lux) Sunlight: 8000 Ft Candles (86,111 Lux)  User-selectable: three levels  User-selectable: three tones  Conforms to 15 kV air discharge  Print Contrast Min.:  Roll (Tilt):  Skew (Yaw):  Pitch:  Skew (Yaw):  Skew (Yaw):  Interface  Supported:  Interfaces Supported:  Interfaces Supported:  Electrical Safety:  Electrical Safety:  EMI/RFI:

The LS1203 is warranted against defects in workmanship and materials for a period of 3 years (36 months) from date of shipment, provided that the product remains unmodified and is operated under normal and proper conditions. See full warranty for details.

1 - Roll (Tilt): Controlled by rotating the wrist clockwise or counterclockwise 2 - Pitch: Controleed by dropping or raising the wrist 3 - Skew (Yaw): Controlled by rotating the wrist from left to right or vice versa 4 - LED lighting with high AC ripple content can impact scanning performance

	DEPTH OF FIELD  LS1203		
Label Density			
Paper Label	English	Metric	
Code 39 – 5 mil	0.25" - 5.00"	0.50 - 12.50 cm	
Code 39 – 7. 5 mil	0 – 7.75"	0 – 19.68 cm	
Code 39 – 10 mil	0 – 8.50"	0 – 21.50 cm	
100% UPC – 13 mil	0 – 8.50"	0 – 21.50 cm	
200% UPC – 26 mil	0 – 10.25"	0 – 26.00 cm	



Part number SS-LS1203-A. Printed in USA 04/15.©2015 ZIH Corp. ZEBRA, the Zebra head graphic and Zebra Technologies logo are trademarks of ZIH Corp, registered in many jurisdictions worldwide. All rights reserved. All other trademarks are the property of their respective owners.

**ZEBRA TECHNOLOGIES**