



www.amlabels.co.uk
sales@amlabels.co.uk
01536 414222

Z-Perform 1000D

Permanent labels

Direct thermal

Description

A white uncoated direct thermal label stock, which produces black visible light images with Zebra thermal printers. The acrylic based adhesive offers good initial tack and adhesion on a wide range of surfaces.

Note: Z-Perform 1000D is not recommended for applications involving long term exposure to sunlight or extreme heat.

Suggested Applications

- Product identification
- Labelling of most packaging materials
- Indoor general purpose labelling
- Warehouse picking and receiving labels
- Shipping labels
- Product and price labelling in Retail
- Bakery/delicatessen labelling

Technical Specifications

| | Description | Caliper |
|-----------|-----------------------------------|-------------------|
| Facestock | 75gsm thermal imaging paper | 83 microns |
| Adhesive | Acrylic based, permanent adhesive | 15 microns |
| Liner | 60gsm glassine liner | 56 microns |
| | | Total 154 microns |

Recommended Zebra printers: Mobile, desktop, mid-range and high-performance thermal printers

Recommended Zebra ribbons: N/A

Minimum application temperature: 0°C

Service temperature range: -20°C to 50°C

Recommended storage conditions: Six months duration when stored at 0°C to 21°C at 35% to 50% RH

Product Performance and Suitability

The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

For testing of this material, please order sample roll SAM65345.