



www.amlabels.co.uk
sales@amlabels.co.uk
01536 414222

Z-Select 2000T

Permanent labels

Thermal transfer

Description

Z-Select 2000T is an ultra smooth topcoated white paper label stock, which produces excellent quality images, including rotated bar codes, graphics and small characters, at print speeds up to 305mm per second. Compatible with Zebra 2100, 2300, 5319 and 3400 ribbons for standard thermal transfer printing. Suitable for use with Zebra 3200 ribbons for applications requiring improved smear and scratch resistance.

Suggested Applications

- Labelling of packaging materials e.g. boxes, pallets in logistics applications
- Picking and receiving labels in the warehouse
- Product identification
- Compliance labelling
- Work in progress labels
- Shipping labels
- Document tracking in government applications
- Sterile services labelling in healthcare applications

Technical Specifications

	Description	Caliper
Facestock	80gsm smooth white topcoated paper	78 microns
Adhesive	Permanent acrylic based	15 microns
Liner	65gsm Glassine liner	56 microns
		Total 149 microns

Recommended Zebra printers: desktop, mid-range and high-performance printers

Recommended Zebra Ribbons: 2300, 2100, 5319, 3400, 3200

Minimum application temperature: 0°C

Service temperature range: -20°C to 80°C

Recommended storage conditions: One year duration when stored at 0°C to 21°C at 35% to 50% RH

Product Performance and Suitability

The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

For testing of this material, order from the Zipship price list or order sample roll SAM5257.